

ADVANCED SYNTHETIC 5W40 SN

DESCRIPTION:

Cerma 5W40 Motor Oil provides high quality engine protection under all driving conditions and is formulated with premium base stocks and a premium additive package to provide extra protection against the harmful effects of city driving, where cars undergo a higher stress due to constant stopping and going.

Cerma 5W40 Motor Oil low friction formula helps improve gas mileage for long engine life and helps protect against rust, corrosion, startup wear, varnish build-up, and eliminates the need for extra oil additives. It also protects against thermal breakdown which helps prevent stuck rings.

FEATURES/BENEFITS:

- Protects engines under all driving conditions
- Lowers friction and improves gas mileage
- Provides longer engine life
- Protects against rust, corrosion and varnish
- Resists thermal break-down

APPLICATIONS:

Cerma 5W40 Motor Oil meets requirements of API SN service. This product is also recommended for older engines, which owner's manual calls for API SN, SM, SL, SJ, SH, SG, SF, SE Service Classifications or any combination thereof. Viscosity recommendations vary according to temperature and engine manufacturer.

* ALWAYS CONSULT YOUR OWNER'S MANUAL FOR THE PROPER FLUID FOR YOUR EQUIPMENT.

TYPICAL TEST DATA

SAE GRADE	5W40
Specific Gravity, (60°F)	0.8608
Viscosity, @ 40°C, cSt	97.6
Viscosity, @ 100°C, cSt	14.1
Viscosity Index	148
Cold Crank, cP at °C, Max	6600 @ -30C
Flash Point, °F	450
Pour Point, °C (°F)	-30 (-22)
Noack Volatility %, Max	15
High Temp/High Shear Visc, cP @150°C, Min	3.5
Color	2.5
Phosphorus, wt%	0.07
Zinc, wt%	0.08

Typical test data are average values only. Minor variations which do not affect product performance are to be expected during normal manufacturing.