

Two-Stroke Pre-Mix Ratio Chart

Mixture Ratio to 1	Percent Oil	Ounces of Oil per Gallon of Gas					
		1 gal	2 gal	2.5 gal	3 gal	4 gal	5 gal
16	6.25	8.00	16.00	20.00	24.00	32.00	40.00
20	5.00	6.40	12.80	16.00	19.20	25.60	32.00
25	4.00	5.12	10.24	12.80	15.36	20.48	25.60
30	3.33	4.27	8.54	10.68	12.81	17.08	21.35
32	3.13	4.00	8.00	10.00	12.00	16.00	20.00
35	2.86	3.66	7.32	9.15	10.98	14.64	18.30
40	2.50	3.20	6.40	8.00	9.60	12.80	16.00
45	2.22	2.84	5.68	7.10	8.52	11.36	14.20
50	2.00	2.56	5.12	6.40	7.68	10.24	12.80
55	1.82	2.33	4.66	5.83	6.99	9.32	11.65
60	1.67	2.13	4.26	5.33	6.39	8.52	10.65
70	1.43	1.83	3.66	4.58	5.49	7.32	9.15
80	1.25	1.60	3.20	4.00	4.80	6.40	8.00
90	1.11	1.42	2.84	3.55	4.26	5.68	7.10
100	1.00	1.28	2.56	3.20	3.84	5.12	6.40

Cerma 2-Cycle Oils are produced using the best base oils and blended with STM-3 additive pack, to protect engine from wear, clean engine, increase usable power, and increase engine life.

Cerma Industries, LLC. Denison, TX www.cermastore.com (800) 917-6762